



CL 1110 BENTONE NON MELT EP GREASE

PRODUCT DESCRIPTION

CL 1110 Bentone Non Melt EP Grease is a special formulate with the selective additives package to achieve the excellent performance toward high temperature and shock load condition. It contain of smooth texture and superior quality additives for industrial lubrication application. It contain of superb EP additives to perform good metal adhesiveness and excellent water resistant. **CL 1110 Bentone Non Melt EP Grease** was not easy wash out by water and absorbed water does not affect consistency. An important property of **CL 1110** is that they do not melt allowing particular applications in steel mills, cement plants, glass plants or where high temperature are likely. This high performance grease offer exceptional performance to the user and satisfy multiple equipment applications.

PRODUCT FEATURES

- Extreme Pressure Additive to prevent shock load
- Rust & Corrosion Protection
- Non melt grease
- Excellent water resistant to prevent water “Wash Out” condition
- Superior tackiness provide complete surface protection
- Applicable to the most industrial machinery, construction applications, electrical motor, bearing and gears.

TYPICAL SPECIFICATION

NLGI Grade	2
Penetration, Wkd 60 Strokes, ASTM D 217	265 – 295
Boiling/Melting Point °C.....	260°C
Specific Gravity.....	0.9450
Vapor Density (air=1).....	Not Determined
Solubility In Water.....	Insoluble
Appearance /Odor.....	Yellowish Light Brown