



CL 2000 SYNTHETIC GEAR OIL PAO BASE

PRODUCT DESCRIPTION

CL 2000 SYNTHETIC GEAR OIL PAO BASE are specially formulated by using refined synthetic base stock which provide numerous benefits, such as exceptionally high oxidation resistance resulting in minimum sludge and varnish formation and increased useful oil life, significant wear reduction, high lubricity, film strength and broad operating temperatures range.

PRODUCT APPLICATION

CL 2000 SYNTHETIC GEAR OIL PAO BASE recommended for used in air compressors, bearings, oil circulating systems, enclosed gear drives and other equipment operating in severe services.

TYPICAL SPECIFICATION

ISO Viscosity	100	220	320	460
VISCOSITY :				
Cst @ 40°C	100	212	302	438
Cst @ 100°C	13.7	25.0	33.0	43.0
SUS @ 100°C	514	1007	1568	2286
SUS @ 210°C	74	123	161	208
Viscosity Index	138	148	151	151
Pour Point , °F	-50	-35	-30	-30
Flash Point , °F	425	430	430	440
Density lbs/gal @ 60°F	7.16	7.33	7.33	7.34
4 Ball Wear , mm	0.40	0.38	0.38	0.37
RBOT Mins	1400+	1400+	1400+	1400+