



CL 3500 PREMIUM HYDRAULIC OIL

PRODUCT DESCRIPTION

CL 3500 Premium Hydraulic Oil is formulated from highly refined hydro-treated base stocks and premium grade hydraulic oil additive package. This product are designed for today's modern hydraulic systems with higher make up rates and sophisticated filtering system.

The additives found in CL 3500 Premium Hydraulic Oil enhance the anti wear characteristics of the fluid. They also inhibit foam from forming in the oil and offer a robust protection against rust and corrosion in the event of water contamination.

CL 3500 Premium Hydraulic Oil are suitable for applications used in hydraulic & pump systems where excellent antiwear performance & superior filterability are essential.

PRODUCT FEATURES

- Prevent wear & tear
- Protect against rust & corrosion
- Anti forming protection & separates readily from water
- High Thermal stability
- Superior filterability

TYPICAL SPECIFICATION

ISO Viscosity	32	46	68	100
SAE Grade	10	15	20	30
Specific GRAVITY, @ 15°C	0.865	0.870	0.872	0.878
VISCOSITY :				
Cst @ 40°C	31.5	46.4	68.5	97.5
Cst @ 100°C	5.4	6.85	8.78	11.27
Viscosity Index	105	103	102	100
Pour Point , °C	-33	-30	-27	-24
Flash Point , °C	210	220	222	228
Appearance	<0.5	<0.5	<0.5	<0.5