



CL 8200 LEAK DETECTOR

PRODUCT DESCRIPTION

CL 8200 Leak Detector are used for detecting leaks in pipe joints, tube connections, tanks or any system under gas or air pressure. They are very easy to use, simply wipe surface to be tested with a brush or dauber, squirt on spray with a trigger sprayer. Small leaks form white foam in 5 to 60 seconds. Large leaks form large bubbles almost instantly.

CL 8200 The first and best chemical type leak detector designed for finding air and gas leaks at subfreezing temperatures down to -5 degrees Fahrenheit

CL 8200 Specially formulated chemical type leak detection fluid for locating leaks in pressurized gas and air systems, except oxygen, in temperatures above freezing.

CL 8200 The first fluid developed specifically for detecting leaks in refrigeration and air-conditioning equipment and systems. Works on the bubbling principle but is not a soap solution and dries clean.

DIRECTION OF USE

Shake the can before spray. Then adjust spray on the suspected leakage surface with reasonable thickness and ensure the surface is fully coverage to prevent unspotted leak. **CL 8200 Leak Detector** will quickly give obvious visual of bubbles foaming.

CAUTION

Do not spray near any fire or sparking point, should stored with temperature below 40°C, If accidentally swallowed, call medical help immediately. Contents under pressure. Do not puncture or incinerate container. Keep out of children.