



CL 9800 ROOFCOTE

DESCRIPTION

CL 9800 Roofcote is a premium grade coating designed to restore weathered concrete roof to look new again. It's tough and durable finish gives long lasting protection against the tropical climate and provides excellent resistance to algae and fungal growth. **CL 9800 Roofcote** outlast ordinary roof paint.

CL 9800 designed use for protection and decoration of old and previously painted cement fibre, metal roof and concrete roof tiles. **CL 9800** is a premium grade acrylic binder with high grade pigments that resist salts on concrete, tile and masonry surfaces.

PERFORMANCE

- ✓ Excellent fungal and algae growth resistant
- ✓ Excellent colour retention
- ✓ Tough synthetic finish - washable
- ✓ No added lead or mercury

PHYSICAL PROPERTIES

Coverage	10 - 12m ² /Lit @ 25 microns
Volume Solid	White 40%, other colour will vary
Dry Film Thickness	25 microns/ coat
Wet Film Thickness	63 microns/ coat
Flash Point	Not applicable

APPLICATION DATA

Drying Time Surface dry: 10 min; Recoat: 1-2 hours

Dilution ratio:

Brush or Roller On hot surface, add up to 20% water.
Cool surface: Ready for use.

Spray Equipment Guide:

Conventional Spray A typical set up would be a minimum atomising pressure of 2.8kg/cm² and fluid pressure of 0.4kg/cm³ with a nozzle size of 0.43mm.

Airless Spray A typical set up would be a minimum of 155kg/cm³ with a nozzle size of 0.38 – 0.43mm and a spray tip angle of 65°.

SURFACE PREPARATION

For concrete roof tiles

Check for fungus and algae growth. If present, do a fungicidal wash (1 part household bleach with 3 parts water). Allow the mixture to penetrate the affected area. Check for leaks and make good all minor cracks with appropriate exterior grade sealants. Use cement mix for larger cracks. When dry, remove all fungi, algae, chalk and loosely adhering contaminants by scrubbing thoroughly with a stiff fibre brush or with high-pressure water-jet. Allow to dry before priming with **CL 9800 Roofcote**.

For metal roof

Using mineral turpentine, remove all grease, wax and surface contaminants. Previously painted surfaces must be thoroughly rubbed down using a suitable abrasive paper and then dusted off.

SAFETY & HEALTH INFORMATION

- Ensure adequate lighting and ventilation during application and drying.
- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical assistance.
- Use soap and water to remove splashes from skin.
- Storage: Keep container closed and store in clean, dry conditions.
- Do not empty into drains or water courses.
- This product is not flammable. Keep out of reach of children.
- Chemical Safety Data Sheet (CSDS) is available upon request.



Keep seal tight



Secure upright



Wear proper
protection



Practice proper
disposal